



## 65W Power Supply adapter for Unicable II™ multiswitches (EU plug)

Model: IDLU-ADPT03-19342-OPP

Item: 5423

This power supply can be used to power up to four cascaded Unicable II™ four-output multiswitches, or up to two cascaded Unicable II™ eight-output multiswitches. It provides overcurrent and short circuit protection and is ideal for buildings/MDU installations of cascaded systems.

### Technical Specifications

Input voltage	100 VAC ~ 240 VAC
Input frequency	50 Hz/60 Hz
Output voltage	19 VDC
Output current	3.42 A
Output connector	F-type (male)
Cable length (AC)	1.8 m
Cable length (DC)	1.5 m
Product dimensions (L x W x H)	11.5 cm x 5.5 cm x 3.5 cm
Working temperature	0 °C ~ +40 °C
Weight	250 g
Compliance	Low Voltage Directive (2014/35/EU) Electromagnetic Compatibility Directive (2014/30/EU) Eco-Design Directive (2009/125/EC)

### Logistical information

Packaging dimensions (h x w x d)	5.8 cm x 9 cm x 15 cm
Packaging weight	0.49 kg
Quantity per carton	50 pcs
Carton dimensions (h x w x d)	49.5 cm x 33 cm x 34.5 cm
Carton weight	24.4 kg
Quantity per pallet	700

For purpose of brevity, some product descriptions in this sheet remain at platform level and may not be referred to as detailed datasheets of the products. Inverto Digital Labs reserves the right to amend, omit or add products, product-lines, and / or features without notice. As product specifications may change without notice, always contact Inverto to obtain the latest product specification sheets.

For further details contact: [sales@inverto.tv](mailto:sales@inverto.tv)

FTA Communication Technologies S.à r.l. Tel. +352 264 367 1 Fax. +352 264 313 68



[www.inverto.tv](http://www.inverto.tv)